

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575 (R.A.)  
Fax +39 02.90394441

[export@sirsafety.com](mailto:export@sirsafety.com)  
[www.sirsafety.com](http://www.sirsafety.com)

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED  
= ISO 9001 =

<b>Name: Flame Retardant Trousers</b>	<b>Code: 33274R</b>	<b>Flame Retardant</b>
---------------------------------------	---------------------	------------------------

### Description

Trousers in 100% Flame Retardant cotton fabric, weight 315 g/m<sup>2</sup>. Metal zipper fly and snap button, two side welt pockets and a rear pocket with flap and snap button.

The trousers shall be worn in combination with the jacket.



- It features remarkable multi-protective properties and is able to guarantee a high level of comfort while maintaining softness, lightness and breathability.
- The complete range can be produced in orange and red colours.

Suitable for protecting the operator from accidental contact with minor flames, molten metal splashes, low values of convective and radiant heat, and accidental electric contact up to 100 V of short duration.

The product is designed and manufactured according to the Directive 89/686/EEC.

It is classified as PPE Cat.II.



Category <b>II</b>	Colours Red	Available Sizes 44-62
Quantity/Carton <b>50</b>	Important Information Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Metalworking Industry, Metallurgical Industry, Foundries, Plastic materials processing, Gas, water and electricity Industries, Firefighting Teams.
Dexterity	EC Standards EN ISO 11611  Class:1 Values:A1  EN ISO 11612  Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E2 Contact Heat:F1	Storage and cleaning We recommend to follow the washing instructions. Resistance up to 25 washings. 